

CAT. No.

80151x10FT

EUROPEAN CEE 7/7 SCHUKO 16 AMPERE 250 VOLT DETACHABLE POWER CORD, (EU1-16P) DIN 49441 ANGLED PLUG, IEC 60320 60320 C-19 STRAIGHT CONNECTOR, 2 POLE-3 WIRE GROUNDING, 3 METERS (10 FT.) LONG. BLACK.


APPROVALS	VDE <input checked="" type="checkbox"/>	CEBEC <input checked="" type="checkbox"/>	DEMKO <input checked="" type="checkbox"/>	FI <input checked="" type="checkbox"/>	IMQ <input checked="" type="checkbox"/>	KEMA <input checked="" type="checkbox"/>	NEMKO <input checked="" type="checkbox"/>	OVE <input checked="" type="checkbox"/>	SEMKO <input checked="" type="checkbox"/>	UTE <input checked="" type="checkbox"/>	
CERTIFICATIONS	REACH <input checked="" type="checkbox"/>	ROHS <input checked="" type="checkbox"/>	CE <input checked="" type="checkbox"/>								
STANDARDS	CEE 7/7 <input checked="" type="checkbox"/>	IEC 60320 C-19 <input checked="" type="checkbox"/>	DIN 49441 <input checked="" type="checkbox"/>								

RELATED POWER CORDS

<u>CATALOG No</u>	<u>LENGTH</u>
80151	2.5 METERS
80151-RA	2.5 METERS
80151-LA	2.5 METERS
80151x6FT	1.8 METERS
80151x10FT	3 METERS
80151x12FT	3.66 METERS
80151x15FT	4.6 METERS

SPECIFICATIONS:

1. OVERALL LENGTH: 3 METERS (10 FT.)
2. CONDUCTORS: 1.5 MM² x 3 (BROWN/BLUE/GREEN-YELLOW)
3. JACKET: H05VV-F, BLACK
4. PLUG: CEE 7/7 ANGLED "SCHUKO" BLACK, DIN 49441
5. CONNECTOR: IEC 60320 C-19, STRAIGHT, BLACK
6. RATED: 16 AMPERE 250 VOLT
7. TEMPERATURE RATING: 70°C
8. CABLE DIAMETER (APPROX.): 7.0 mm
9. GENERAL MATERIAL: PVC
10. STRANDING (APPROX.): 32/0.2 mm
11. OPERATING TEMPERATURE: -15°C TO +70°C



EU1-16P, CEE 7/7
ANGLED "SCHUKO"

IEC 60320, C-19