



CAT. No.

90540

"UNIVERSAL" POWER CORD, IEC 60320 C-20 PLUG, C-19 CONNECTOR, 15 AMPERE 250 VOLT (UL/C-UL), 16 AMPERE 250 VOLT (VDE), SJTO, 105°C, (14/3 AWG, 3x2.08mm²) - (H05VV-F, 1.5 mm²), 2 POLE-3 WIRE GROUNDING (2P+E), 1.0 METERS (3FT.-3IN.) LONG. BLACK.

APPROVALS	C(UL)US <input checked="" type="checkbox"/>	VDE <input checked="" type="checkbox"/>	ENEC 05 <input checked="" type="checkbox"/>	KEMA <input checked="" type="checkbox"/>	RCM MARK <input checked="" type="checkbox"/>
CERTIFICATIONS	REACH <input checked="" type="checkbox"/>	ROHS <input checked="" type="checkbox"/>	ROHS2 <input checked="" type="checkbox"/>	CE <input checked="" type="checkbox"/>	
STANDARDS	IEC 60320 <input checked="" type="checkbox"/>				

CONFIGURATIONS		
RECEPTACLE	PLUG	
		15 AMPERE 250 VOLT UL/CSA
IEC 60320 C-19	IEC 60320 C-20	16 AMPERE 250 VOLT INTERNATIONAL

SPECIFICATIONS:

1. OVERALL LENGTH: 1.0 METERS (3FT.-3IN.)
2. CONDUCTORS: 14/3 AWG, 3x2.08mm² - H05VV-F, 1.5 mm²
3. JACKET: H05VV-F (SJTO), 105°C, BLACK
4. PLUG: IEC 60320 C-20, STRAIGHT, BLACK
5. CONNECTOR: IEC 60320 C-19, STRAIGHT, BLACK
6. RATED: 15/16 AMPERE 250 VOLT

