

CAT. No.

81131x20FT

EUROPEAN CEE 7/7 SCHUKO 10 AMPERE 230-250 VOLT DETACHABLE POWER CORD, (EU-16P) DIN 49441 PLUG, IEC 60320 C-13 STRAIGHT CONNECTOR, 2 POLE-3WIRE GROUNDING, 6.1 METERS (20 FT) LONG. BLACK.

APPROVALS	CEBEC <input checked="" type="checkbox"/>	KEMA <input checked="" type="checkbox"/>	NEMKO <input checked="" type="checkbox"/>	OVE <input checked="" type="checkbox"/>	SEMKO <input checked="" type="checkbox"/>	VDE <input checked="" type="checkbox"/>
STANDARDS	CEE 7/7 <input checked="" type="checkbox"/>					
CERTIFICATIONS	CE <input checked="" type="checkbox"/>	ROHS <input checked="" type="checkbox"/>				

RELATED POWER CORDS

<u>CATALOG No</u>	<u>LENGTH</u>
81131x1FT	12 INCHES
81131x2FT	24 INCHES
81131x3FT	36 INCHES
81131x4FT	48 INCHES
81131x5FT	60 INCHES
81131x6FT	72 INCHES
81131x10FT	120 INCHES
81131x15FT	180 INCHES
81131x20FT	240 INCHES
81131x1M	1 METER
81131x1.5M	1.5 METERS
81131x2M	2 METERS
81131	2.5 METERS
81131x3M	3 METERS
81131x5M	5 METERS
81131-RA	2.5 METERS
81131-LA	2.5 METERS

SPECIFICATIONS:

1. OVERALL LENGTH: 6.1 METERS (20 FT)
2. CONDUCTORS: 1.0 MM x 3 WITH IEC COLOR CODE
3. JACKET: H05VV-F, BLACK
4. PLUG: CEE 7/7 "SCHUKO"
5. CONNECTOR: IEC 60320 C-13, STRAIGHT, BLACK
6. RATED: 10 AMPERE 250 VOLT
7. TEMPERATURE RATING: 70°C
8. CABLE DIAMETER (APPROX.): 7.0 MM
9. GENERAL MATERIAL: PVC
10. STRANDING (APPROX.): 32/.02 MM
11. OPERATING TEMPERATURE: -15°C TO +70C

